

ATEX Compliant Process Pump

Automatically operated type (Internal switching type)/

Air operated type (External switching type)

Series 56-PA3000/5000



CE	Ex	For 56-PA3□□0: II3G Ex h IIB T6 Gc
		II3D Ex h IIIB T68°C Dc
		For 56-PA3□□3: II3G Ex h IIB T5 Gc
		II3D Ex h IIIB T89°C Dc
		For 56-PA5□□0: II3G Ex h IIB T6 Gc
		II3D Ex h IIIB T68°C Dc
For 56-PA5□□3: II3G Ex h IIB T6 Gc		
II3D Ex h IIIB T78°C Dc		
0°C ≤ Ta ≤ +60°C		

How to Order

56-PA 3 1 1 0 - 03 -

ATEX category 3

Body size

Symbol	Body size
3	3/8 standard
5	1/2 standard

Liquid contact body material

Symbol	Body material
1	ADC12 (Aluminum)
2	SCS14 (Stainless steel)

Diaphragm material

Symbol	Diaphragm material	Applicable model	
		Automatically operated type	Air operated type
1	PTFE	●	●
2	NBR	●	—

* Dimensions are the same as the standard products.

Actuation

Symbol	Actuation
0	Automatically operated type
3	Air operated type

Options

Symbol	Options	Applicable model	
		Automatically operated type	Air operated type
Nil	None	●	●
N	With silencer	●	—

Port size

Symbol	Port size	Applicable model	
		PA3000	PA5000
03	3/8"	●	—
04	1/2"	—	●
06	3/4"	—	●

Thread type

Symbol	Type
Nil	Rc
N	NPT
F	G
T	NPTF

All other specifications are the same as the standard products Series PA3000/5000. [Click here](#) for details.